

## Declaration on environmental compatibility in the fields of EMC<sup>1)</sup>, climate and mechanical stress

RE 30156-U/05.09 1/4

**Type VT-MAC8-1X**

Multi-Axis Motion Control

### **Product types**

– VT-MAC8-1X according to data sheet RE 30156

### **Description of the product family**

---

MAC-8 is the digital Rexroth Multi-Axis Motion Control for hydraulic applications. It has a modular design consisting of one master card without axis controller and/or with two or four axis controllers and can be extended as and when required with up to seven slave cards for four axes each to up to 32 axes.

<sup>1)</sup> In the sense of the EMC law of 30th August 1995 and Directive 89/336/EEC

**The products comply with the following standards:****1. EMC** (electromagnetic compatibility)

Testing in accordance with generic standard EN 61000-6-2:2001, VDE 0839 part 6-2 Interference immunity

EN 61000-4-2:1995 +A1:1998 +A2:2000 IEC 1000-4-2	VDE 0847-4-2	ESD (electrostatic discharge)	Air discharge: Severity 3 / assessment criterion A Contact discharge: Severity 4 / assessment criterion A
EN 61000-4-3:2006		HF fields	Severity 3 / assessment criterion A 80 MHz...2,7 GHz
EN 61000-4-4:2004 IEC 1000-4-4	VDE 0847-4-4	BURST (transient discharge)	Repetition rate 5 kHz: Supply voltage: Severity 3 / assessment criterion A Data cables:Severity 4 / assessment criterion A  Repetition rate 100 kHz: Supply voltage: Severity 3 / assessment criterion A Data cables: Severity 4 / assessment criterion A
EN 61000-4-5:1995 +A1:2001 IEC 1000-4-5	VDE 0847-4-5	SURGE (surge voltages)	Supply voltage: Severity 1 / assessment criterion A Data cables: Severity 2, asymmetrical / assessment criterion A
EN 61000-4-6:1996 +A1:2001 IEC 1000-4-6	VDE 0847-4-6	HF fields, conducted interference	Severity 3 / assessment criterion A

Testing in accordance with generic standard EN 61000-6-4:2001, VDE 0839 part 6-4 (Emission)

EN 55011:1998 +A1:1999 +A2:2002	VDE0875-11	Emission Radio interference voltage	Class A / 0,15...30 MHz
---------------------------------------	------------	--	-------------------------

Testing in accordance with generic standard EN 61000-6-3:2001, VDE 0839 part 6-3 (Emission)

EN 55022:1998 +A1:2000 +A2:2003	VDE0875-22	Emission Radio interference voltage	Class B / 0,15...30 MHz when using the power supply unit VT-NE40 (mat. no. R900782039)
EN 55022:1998 +A1:2000 +A2:2003 IEC 1000-4-2	VDE0878-22	Emission Radio interference voltage	Class B / 30...1000 MHz
EN 55011:1998 +A1:1999 +A2:2002 IEC 1000-4-2	VDE0875-11	Emission Radio interference voltage	Class B / 1...18 GHz

**The products comply with the following standards:****2. Klima**

Testing in accordance with EN 60068-2 / IEC 68-2 (environmental testing)

EN 60068-2-1:1994		Cold test	2 cycles -5 °C Dwell time 2 hours
EN 60068-2-2:1993		Dry heat test	2 cycles +55 °C Dwell time 2 hours
EN 60068-2-1:1994 EN 60068-2-2:1993		Storage temperature	-25 °C, dwell time 16 hours +85 °C, dwell time 16 hours
	IEC 68-2-14:1986	Temperatur cycle	2 cycles -5 °C to +55 °C Dwell time 3 hours each at min. / max. temperature
EN 60068-2-30:1999		Damp heat, cyclical	Variant 2 +25 °C to +40 °C 93 % to 97 % relative humidity 2 cycles 24 hours each

**3. Mechanical stress**

Vibration and shock test in accordance with EN 60068-2 / IEC 68-2 / DIN 40046 (environmental testing)

Testing in three axes (X/Y/Z)

EN 60068-2-6:1996			Sine test	20 cycles, 5...500 Hz at a logarithmic frequency change rate of 1 oct./min. 5 to 57 Hz, amplitude 0.3 mm (p-p) 57 to 500 Hz, amplitude 2 g
	IEC 68-2-36:1973	DIN 40046-24:1977	Random test Wide band noise	20 to 500 Hz, amplitude 0,01 g <sup>2</sup> / Hz (2.2 g RMS) Testing time 30 min
EN 60068-2-27:1993			Shock test	Half sine 15g / 11 ms, 3 x in positive/ 3 x in negative direction per axis; in total, 18 individual shocks

## Notizen

---

© This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth AG. It may not be reproduced or given to third parties without its consent. The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. It must be remembered that our products are subject to a natural process of wear and aging.

